

SAFETY DATA SHEET DOMINATOR® Octane Boost

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification

Product identifier

Product name DOMINATOR® Octane Boost

Product number AOB, COB

Recommended use of the chemical and restrictions on use

Application Fuel additive.

Uses advised against Avoid the formation of mists.

Details of the supplier of the safety data sheet

Supplier AMSOIL INC.

Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4

T: +1 416-367-6547

Manufacturer AMSOIL INC.

One AMSOIL Center, Superior, WI 54880, USA. T: +1 715-392-7101

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300

Outside the USA and Canada: +1 703-741-5970

(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

OSHA/WHMIS Regulatory

This Product is Hazardous under the OSHA Hazard Communication Standard and according

to the hazard criteria of the Hazardous Product Regulations.

Physical hazards Flam. Liq. 4 - H227

Health hazards Acute Tox. 4 - H302 Acute Tox. 2 - H330 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 -

H373 Asp. Tox. 1 - H304

Environmental hazards Aquatic Acute 2 - H401 Aquatic Chronic 2 - H411

Label elements

Pictogram

Status









Signal word

Danger

DOMINATOR® Octane Boost

Hazard statements H227 Combustible liquid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H330 Fatal if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P102

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P260 Do not breathe vapor/ spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves, eye and face protection.

P284 [In case of inadequate ventilation] wear respiratory protection. P301+P310 If swallowed: Immediately call a poison center/ doctor.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P308+P313 If exposed or concerned: Get medical advice/ attention.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Hydrogenated base oil, Methylcyclopentadienyl manganese tricarbonyl

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Hydrogenated base oil 94.0 - 96.0%

CAS number: 68476-34-6

Classification

Flam. Liq. 4 - H227 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Carc. 2 - H351 STOT RE 2 - H373

Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

DOMINATOR® Octane Boost

M factor (Chronic) = 1

Methylcyclopentadienyl manganese tricarbonyl

2.0 - 4.0%

CAS number: 12108-13-3

M factor (Acute) = 1

Classification

Acute Tox. 3 - H301 Acute Tox. 2 - H310

Acute Tox. 1 - H330 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Hydrogenated base oil

1.0 - 2.5%

CAS number: 64742-94-5

Classification

Skin Irrit. 2 - H315

STOT SE 3 - H336

Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

Naphthalene 0.07 - 0.7%

CAS number: 91-20-3

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Acute Tox. 4 - H302

Carc. 2 - H351

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Tricarbonyl(η-cyclopentadienyl)manganese

0.01 - 0.04%

CAS number: 12079-65-1

Classification

Acute Tox. 2 - H300

Acute Tox. 1 - H330

Skin Irrit. 2 - H315

STOT SE 1 - H370

STOT RE 2 - H373

DOMINATOR® Octane Boost

1,2,4-Trimethylbenzene 0.03 - 0.2%

CAS number: 95-63-6

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411

Mesitylene 0.005 - 0.015%

CAS number: 108-67-8

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

STOT SE 3 - H335

Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin Contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or

wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

DOMINATOR® Octane Boost

Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Difficulty in breathing.

Unconsciousness, possibly death. Prolonged or repeated exposure may cause the following

adverse effects: Suspected of causing cancer.

Ingestion May cause discomfort if swallowed. Stomach pain. Nausea, vomiting. Aspiration hazard if

swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Prolonged or repeated exposure may cause the following adverse effects:

Suspected of causing cancer.

Skin contact Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse

effects: Suspected of causing cancer.

Eye contact May cause temporary eye irritation.

Indication of immediate medical attention and special treatment needed

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is combustible. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. This

product is toxic.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Very toxic gases or vapors. Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2). Oxides

of nitrogen. Metal oxide(s).

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

DOMINATOR® Octane Boost

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapors and spray/mists. Use suitable respiratory protection if ventilation is inadequate.

Environmental precautions

Environmental precautions

Toxic to aquatic life with long lasting effects. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Provide adequate ventilation. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is combustible. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapors may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. This product is toxic. Immediate first aid is imperative. Suspected of causing cancer. Avoid discharge to the aquatic environment. Avoid contact with used product. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

DOMINATOR® Octane Boost

Storage precautions Store away from incompatible materials (see Section 10). Store locked up. Eliminate all

sources of ignition. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed,

in a cool, well ventilated place. Protect containers from damage.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Hydrogenated base oil

Long-term exposure limit (8-hour TWA): ACGIH 100 mg/m³ inhalable fraction and vapor as total hydrocarbons

A3, Sk

Methylcyclopentadienyl manganese tricarbonyl

Long-term exposure limit (8-hour TWA): ACGIH 0.2 mg/m³ as Mn Sk

Naphthalene

Long-term exposure limit (8-hour TWA): OSHA 10 ppm 50 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 10 ppm 52 mg/m³ A3, DSens, Sk

Tricarbonyl(η-cyclopentadienyl)manganese

Long-term exposure limit (8-hour TWA): ACGIH 0.1 mg/m³ as Mn Sk

1,2,4-Trimethylbenzene

Long-term exposure limit (8-hour TWA): ACGIH 25 ppm 123 mg/m³

Mesitylene

Long-term exposure limit (8-hour TWA): ACGIH 25 ppm 123 mg/m³ ACGIH = American Conference of Governmental Industrial Hygienists. OSHA = Occupational Safety and Health Administration. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans. Sk = Danger of cutaneous absorption. DSens = Dermal sensitizer.

Ingredient comments

The constituents listed are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Naphthalene (CAS: 91-20-3)

Immediate danger to life 250 ppm and health

Exposure controls

DOMINATOR® Octane Boost

Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eve/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. It is recommended that gloves are made of the following material: Neoprene. Nitrile rubber. Polyvinyl alcohol (PVA). Polyvinyl chloride (PVC).

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Organic vapor filter. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Gas and combination filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

AppearanceLiquid.ColorRed.OdorPetroleum.

DOMINATOR® Octane Boost

Odor threshold Not available.pH Not available.Melting point Not available.

Initial boiling point and range Not available.

Flash point > 60.6°C Pensky-Martens closed cup. [ASTM D 93]

Evaporation rate Not available.

Upper/lower flammability or

explosive limits

Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 0.817 - 0.903 @ 21.1°C/70°F

Solubility(ies)

Partition coefficient

Not available.

Auto-ignition temperature

Not available.

Decomposition Temperature

Not available.

Viscosity 2.36 cSt @ 40°C [ASTM D 445]

Explosive properties Not considered to be explosive.

Oxidizing properties Does not meet the criteria for classification as oxidizing.

Other information No information required.

10. Stability and reactivity

Reactivity See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidizing agents.

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurize, cut, weld, drill, grind or otherwise expose containers to

heat or sources of ignition.

Materials to avoid Oxidizing materials. Acids - oxidizing. Inorganic nitrates. Chlorine. Fluorine.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapors. Carbon

dioxide (CO2). Carbon monoxide (CO). Nitrous gases (NOx). Metal oxides.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Acute Tox. 4 - H302 Harmful if swallowed.

DOMINATOR® Octane Boost

ATE oral (mg/kg) 1,295.0

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 3,500.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Acute Tox. 2 - H330 Fatal if inhaled.

4.36

ATE inhalation (vapours mg/l) 1.9

ATE inhalation (dusts/mists

mg/l)

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitizationBased on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Suspected of causing cancer.

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly

carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the

result if vomited material containing solvents reaches the lungs.

General information May cause cancer after repeated exposure. Risk of cancer depends on duration and level of

exposure. The severity of the symptoms described will vary dependent on the concentration

and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Difficulty in breathing.

Unconsciousness, possibly death.

SAVE UP TO 25%

Supersedes date: 8/23/2016

DOMINATOR® Octane Boost

Ingestion May cause discomfort if swallowed. Stomach pain. Nausea, vomiting. Aspiration hazard if

swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Skin Contact Redness. Irritating to skin.

Eye contact May cause temporary eye irritation.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target Organs No specific target organs known.

Toxicological information on ingredients.

Hydrogenated base oil

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 17900 mg/kg, Oral, Rat REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o > 4300 mg/kg, Dermal, Rabbit REACH dossier information.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l)

4.1

Species Rat

Notes (inhalation LC₅₀) 4 hours REACH dossier information.

4.1

ATE inhalation

(dusts/mists mg/l)

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Severe erythema (beef

redness) to eschar formation preventing grading of erythema (4). Edema score: Moderate oedema - raised approximately 1 mm (3). REACH dossier information.

Irritating.

Serious eye damage/irritation

Serious eye Dose: 0.1 ml, 30 seconds, Rabbit Cornea score: 0 Iris score: 0 Conjunctivae score:

damage/irritation 0 REACH dossier information. Not irritating.

Skin sensitization

Skin sensitization Buehler test - Guinea pig: Not sensitizing. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative. REACH dossier information.

Genotoxicity - in vivoGene mutation: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

fertility

:

Two-generation study - NOAEL 1000 mg/kg/day, Oral, Rat F1 REACH dossier

Developmental toxicity:, Maternal toxicity: - NOAEL: 125 mg/kg/day, Dermal, Rat

information.

Reproductive toxicity -

REACH dossier information.

development

Specific target organ toxicity - repeated exposure

DOMINATOR® Octane Boost

STOT - repeated exposure NOAEC > 1.71 mg/l, Inhalation, Rat REACH dossier information.

Target organs Thymus Liver bone marrow

Methylcyclopentadienyl manganese tricarbonyl

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

51.8

Species Rat

Notes (oral LD₅₀) Toxic if swallowed.

ATE oral (mg/kg) 51.8

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 140.0

mg/kg)

Species Rabbit

Notes (dermal LD₅₀) Toxic in contact with skin.

ATE dermal (mg/kg) 140.0

Acute toxicity - inhalation

Acute toxicity inhalation 0.0

(LC₅₀ vapours mg/l)

0.076

Species Rat

Notes (inhalation LC50) Fatal if inhaled.

ATE inhalation (vapours

mg/l)

0.076

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Germ cell mutagenicity

Genotoxicity - in vitro Bacterial reverse mutation test: Negative. Based on available data the classification

criteria are not met.

Genotoxicity - in vivo Micronucleus assay: Negative. Based on available data the classification criteria

are not met.

12. Ecological Information

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrogenated base oil

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 21 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EL50, 48 hours: 68 mg/l, Daphnia magna

DOMINATOR® Octane Boost

Acute toxicity - aquatic

plants

EL₅₀, 72 hours: 22 mg/l, Pseudokirchneriella subcapitata

Methylcyclopentadienyl manganese tricarbonyl

Toxicity Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 Very toxic to aquatic life with long

lasting effects.

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 0.83 mg/l, Daphnia magna NOEC, 48 hours: 0.29 mg/l, Daphnia magna

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Degradability Non-rapidly degradable

M factor (Chronic)

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Hydrogenated base oil

Biodegradation Water - Degradation 57.5%: 28 days

Not readily biodegradable.

Methylcyclopentadienyl manganese tricarbonyl

Persistence and

degradability

The product is biodegradable.

Biodegradation Water - Degradation 46%: 28 days

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Methylcyclopentadienyl manganese tricarbonyl

Partition coefficient log Kow: 3.7

Mobility in soil

Mobility No data available.

Ecological information on ingredients.

Methylcyclopentadienyl manganese tricarbonyl

Mobility The product is soluble in water.

DOMINATOR® Octane Boost

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Vapor from residual product may create a highly flammable or explosive atmosphere inside the container. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not cut or weld used containers unless they have been thoroughly cleaned internally.

14. Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

UN Number

UN No. (TDG) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082
UN No. (DOT) NA1993

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

Hydrogenated base oil, Methylcyclopentadienyl manganese tricarbonyl)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

Hydrogenated base oil, Methylcyclopentadienyl manganese tricarbonyl)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

Hydrogenated base oil, Methylcyclopentadienyl manganese tricarbonyl)

Proper shipping name (DOT) COMBUSTIBLE LIQUID, N.O.S. (CONTAINS Hydrogenated base oil, Methylcyclopentadienyl

manganese tricarbonyl)

Transport hazard class(es)

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9

DOMINATOR® Octane Boost

Transport labels



Packing group

TDG Packing Group

IMDG packing group III

ICAO packing group

DOT packing group

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation

(SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

The following ingredients are listed or exempt:

Methylcyclopentadienyl manganese tricarbonyl EPCRA 302 TPQ 100 lbs Tier II TPQ 100 lbs

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Naphthalene

Final CERCLA RQ: 100(45.4) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

The following ingredients are listed or exempt:

Methylcyclopentadienyl manganese tricarbonyl

EPCRA RQ: 100 lbs

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

DOMINATOR® Octane Boost

1,2,4-Trimethylbenzene

1.0 %

Methylcyclopentadienyl manganese tricarbonyl

10%

Naphthalene

0.1 %

Tricarbonyl(η-cyclopentadienyl)manganese

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Naphthalene

Known to the State of California to cause cancer.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

1,2,4-Trimethylbenzene

Naphthalene

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Methylcyclopentadienyl manganese tricarbonyl

Naphthalene

Tricarbonyl(η-cyclopentadienyl)manganese

Mesitylene

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

1,2,4-Trimethylbenzene

Methylcyclopentadienyl manganese tricarbonyl

2-Ethylhexan-1-ol

Naphthalene

 $Tricarbonyl(\eta$ -cyclopentadienyl)manganese

Mesitylene

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

DOMINATOR® Octane Boost

Methylcyclopentadienyl manganese tricarbonyl

Naphthalene

Tricarbonyl(η-cyclopentadienyl)manganese

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

1,2,4-Trimethylbenzene

Methylcyclopentadienyl manganese tricarbonyl

Naphthalene

Tricarbonyl(η-cyclopentadienyl)manganese

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

1,2,4-Trimethylbenzene

Methylcyclopentadienyl manganese tricarbonyl

Naphthalene

 $Tricarbonyl(\eta$ -cyclopentadienyl)manganese

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

1,2,4-Trimethylbenzene

Methylcyclopentadienyl manganese tricarbonyl

2-Ethylhexan-1-ol

Naphthalene

 $Tricarbonyl(\eta$ -cyclopentadienyl)manganese

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

DOMINATOR® Octane Boost

Abbreviations and acronyms used in the safety data sheet

C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose, Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very

Classification abbreviations

and acronyms

Acute Tox. = Acute toxicity
Asp. Tox. = Aspiration hazard
Carc. = Carcinogenicity
Skin Irrit. = Skin irritation

Bioaccumulative.

STOT RE = Specific target organ toxicity-repeated exposure Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

 Revision date
 11/2/2017

 Supersedes date
 8/23/2016

SDS No. 6385

Hazard statements in full H226 Flammable liquid and vapor.

H227 Combustible liquid. H300 Fatal if swallowed. H301 Toxic if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H310 Fatal in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation.

H330 Fatal if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H370 Causes damage to organs (Lungs, Nervous system).

H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure. H373 May cause damage to organs (Thymus, Liver, bone marrow) through prolonged or

repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life. H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.