

BUY ONLINE

SAVE UP TO 25% OFF



TEAM AMSOIL
Tim Tremblay
2X AMSOIL Championship
Snocross Series Pro Lite Champ
2013 Winter X Games Medalist
2012 AMSOIL Championship
Snocross Series Pro Open Champ



Contact your local full-service AMSOIL Dealer for more information on AMSOIL products or to place an order. You may also order direct by calling AMSOIL INC. at 1-800-956-5695 and providing the referral number listed here. ▼

Referral # _____



SYNTHETIC 2-STROKE OIL

SYNTHETIC 4-STROKE OIL

ACCESSORY PRODUCTS



Order by Phone 1-800-956-5695 - Give Operator Reference #6068484



Snowmobiles are meant to be ridden hard. Pushing a sled to wide-open throttle during all-day, aggressive riding, however, can result in engine wear and even reduced engine life if your oil isn't able to withstand this intense environment. AMSOIL synthetic lubricants are designed in the lab, proven in the field and validated on the race course. They withstand the toughest operating conditions, delivering peace of mind that your sled is protected no matter how hard you ride.

- **Maximum** wear protection
- **Advanced** cold-temperature performance
- **Superior** deposit control
- **Excellent** for Polaris*, Ski-Doo* (E-TEC*), Arctic Cat* (C-TEC*), Yamaha* & more



AMSOIL synthetic two- and four-stroke oils are Warranty Secure™, keeping your factory warranty intact. For details, visit www.amsoil.com/warrantysecure.

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are developed by AMSOIL for use in snowmobiles.

BUY ONLINE



AMSOIL Synthetic Chaincase & Gear Oil

Difficult access makes chaincase and gearcase service easy to overlook. AMSOIL Synthetic Chaincase & Gear Oil stays fluid in sub-zero cold to reduce drag and maximize power. Its extreme-pressure additives deliver long-lasting wear protection, even if service is delayed.

- **Long-lasting** wear protection
- **Maximizes** power to the ground
- **Recommended** for virtually all brands, including Arctic Cat* Diamond Drive* Gearcases

SAVE UP TO 25% G



AMSOIL Quickshot®

- **Cleans** fuel systems
- **Addresses** ethanol-related performance issues
- **Stabilizes** fuel



AMSOIL Synthetic Water-Resistant Grease

- **Resists** water washout
- **Fights** corrosion

AMSOIL Storage Products

AMSOIL Gasoline Stabilizer reduces the oxidation process in gasoline to help prevent harmful varnish and gum buildup, keeping fuel fresh up to 12 months.

AMSOIL Engine Fogging Oil resists rust formation during storage or long periods of inactivity, guarding against wear-causing dry starts.



Three Top Snowmobile Brands. One Exceptional Oil.

During the winter of 2015/16, AMSOIL INTERCEPTOR® Synthetic 2-Stroke Oil was tested in the three top makes of snowmobiles. Each sled was added to the rental fleet of a different outfitter in the Eagle River, Wis., area and placed into real-world service. Typical riding conditions included frequent throttle bursts; all-day, aggressive riding and the general wear and tear endured by rental equipment. In all three makes, INTERCEPTOR completely prevented piston ring sticking, piston scuffing and exhaust power valve sticking, helping maximize performance and engine life.



Arctic Cat® ZR 6000
(2,000 miles)



Polaris® Indy 600
(1,116 miles)



Ski-Doo® MXZX 600 TNT
(1,327 miles)



AMSOIL Suspension Fluid

- Controls friction & heat
- Limits shock fade and inconsistent dampening
- Light #5: Quick rebounds under extreme temperatures
- Medium #10: More dampening & slower rebounds

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are developed by AMSOIL for use in the applications shown.

Order by Phone 1-800-956-5695 - Give Operator Reference #6068484

• NO PISTON RING STICKING
• NO PISTON SCUFFING